



Helping to protect lives globally

Jo**Bird**®

BUILT BY **THE BEST** TO
WITHSTAND **THE WORST.**

Product **data sheet**

JB02HS Swinging hose reel cabinet



Typical use:

For the storage of 1 x swinging hose reel assembly (not included). This can be fitted to the back wall or either side which are then suitably reinforced to take the weight. These are for on and offshore use. It is widely used by the world's top energy company due to its durability.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for the fire Hoses in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The door can be specified with left or right hinging and features a nylon rod handle to pull the door open to guarantee fast access in an emergency even when wearing gloves.

Standard specification:

Dimensions :Height x width x depth:

930 x 812 x 344 mm (36.6 x 32 x 13.5")

Aperture: 755H x 630W mm (29.7 x 24.8")

Internal depth: 275 mm (10.8")

Weight : 15Kg (33Lb)

Material specification:

Colour: Red RAL 3000

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: 316 Stainless steel

Handle: Nylon Rod

Seal: EPDM

Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window



Manufactured under license in Dubai