



Helping to protect lives globally

Jo**Bird**®

BUILT BY **THE BEST** TO
WITHSTAND **THE WORST.**

Product **data sheet**

JB13.460BA Breathing Apparatus cabinet



Typical use:

For the storage of 1 X 30 to 60 minute full duration breathing apparatus (SCBA) and 1 x spare bottle. Designed for use on and offshore. It is widely used by the world's top energy companies due to its durability.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

Comes fitted with a sprung clip to hold the SCBA and a nylon strap with quick release for the spare bottle.

The door can be specified with left or right hinging and features a nylon rod handle to pull the door open to guarantee fast access in an emergency even when wearing gloves.

Standard specification:

Dimensions (mm)

Height x width x depth: 942 x 572 x 483

Aperture: 757H x 365W

Internal depth: 410

Weight Kg: 12Kg

Material specification:

Colour: Green RAL 6029

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: 316 Stainless steel

Handle: Nylon Rod

Seal: EPDM

Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window

Heating

316 Stainless steel L handle

Vents

Manufactured in the UK

