



Helping to protect lives globally

Jo**Bird**®

BUILT BY **THE BEST** TO
WITHSTAND **THE WORST.**

Product **data sheet**

JB64 Horizontal Fire Hose Cabinet



Typical use:

For the storage of a horizontal Fire Hose reel. This cabinet is widely used in the Offshore energy and marine sectors.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The door can be specified with left or right hinging and features a polyamide handle to pull the door open to guarantee fast access even when wearing gloves.

Standard specification:

Dimensions: Height x width x depth:	1000 x 1050 x 850 mm (39.4 x 41.3 x 33.5")
Aperture:	793H x 833W mm (31.2 x 32.8")
Internal depth:	796 mm (31.3")
Weight :	28 Kg (61.6Lb)

Material specification:

Colour:	Red RAL 3000
Material:	Lloyds approved composites with UV stabilised gelcoat
Hinges:	316 Stainless Steel
Handle:	Polyamide
Seal:	EPDM

Optional Extras:

Other RAL colours
Class 1 fire retardant composites
Perspex window with bezel
3 way locking with stainless steel L handle
Double doors



Lloyd's
Register



Manufactured in the UK