



Helping to protect lives globally

Jo**Bird**®

BUILT BY **THE BEST** TO
WITHSTAND **THE WORST.**

Product **data sheet**

PB10 FEL Emergency Ladder Chest



Typical use:

For the storage of 1 x Fibrelight emergency disembarkation ladder. This chest is widely used in the Offshore energy and marine sectors.

Description:

These chests are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges and catches are secured with 316 stainless steel nuts, bolts and washers.

Standard specification:

Dimensions: 511 x 970 x 630 mm (Height x width x depth)

20.12 x 38.19 x 24.8 inches

Aperture: 925H x 584W mm (36.42 x 22.99")

Internal depth: 484 mm (19.06")

Weight Kg: 43Kg (94.6Lb)

Material specification:

Colour: Orange RAL 2009

Material: Lloyds approved composites with UV stabilised gelcoat

Hinge: Stainless Steel piano hinge

Lettering: "Emergency ladder" 50mm white

Lid catch: 316 Stainless Steel over centre clips

Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Different channel/angle for mountings to decks

Manufactured in the UK

