



Helping to protect lives globally

Jo**Bird**®

BUILT BY **THE BEST** TO
WITHSTAND **THE WORST.**

Product **data sheet**

JB85 Hydrant Equipment Cabinet



Typical use:

For the storage of 1 x of 20m firehose and nozzle. This cabinet is widely used in the Offshore energy and marine sectors.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are manufactured in 316 stainless steel.

The door can be specified with left or right hinging and features a rotary graphite nylon handle to enable fast access even when wearing gloves. An anti-tamper seal can be added.

Standard specification:

Dimensions (mm)

Height x width x depth: 613 x 670 x 185

Aperture: 460H x 520W

Internal depth: 144

Weight Kg: 9Kg

Material specification:

Colour: Red RAL 3000

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges and hose pin: 316 Stainless steel

Handle: Rotary graphite nylon with anti-tamper seal & Biomaster® anti-microbial additive

Seal: EPDM

Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window

Ground mounting posts

Manufactured in the UK

