



Helping to protect lives globally

Jo**Bird**®

BUILT BY **THE BEST** TO
WITHSTAND **THE WORST.**

Product **data sheet**

JB10 Duofold® Stretcher Cabinet



Typical use:

This cabinet is designed to store the Duofold folding stretcher. The wider door aperture of the JB10 when compared to the JB14, makes extracting this type of stretcher from the cabinet very quick and easy. This type of cabinet is widely used on and offshore.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The door can be specified with left or right hinging and features a nylon rod handle to pull the door open to guarantee fast access even when wearing gloves.

Standard specification:

Dimensions : Height x width x depth:

1304 x 788 x 469 mm (51.34 X 31.02 X 18.46")

Aperture: 1052H x 570W mm (41.42 x 22.44")

Internal depth: 415 mm (16.34")

Weight : 22Kg (48.4Lb)

Material specification:

Colour: Green RAL 6029

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: 316 Stainless steel

Handle: Nylon Rod

Seal: EPDM

Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window with bezel

316 Stainless steel 3 way locking

Heating and insulation

Manufactured in the UK

